

## AOT "DU" TYPE ROTARY SLIPS

The AOT "DU" Rotary slips are designed for long trouble free service. They are made of alloy steel and heat-treated for strength and resistance to wear. Both slips are for use in API tapered bowls. The AOT "DU" regular has a 12" long gripping surface and is designed for wells 8000' or less. The AOT "DU" Long has a 16" long gripping surface and is designed for deep wells and heavier drill strings.



AOT#	SLIP BODY SIZE	TYPE	REF#	WT.
03-114	4 1/2"	DU/REGULAR	7613-59	123.00
03-115	4 1/2"	DU/LONG	7613-64	150.00
03-116	5 1/2"	DU/REGULAR	7613-60	128.00
03-117	5 1/2"	DU/LONG	7613-65	162.00
03-118	7"	DU/REGULAR	7613-62	132.00
03-119	7"	DU/LONG	7313-66	192.00



### REPLACEMENT PARTS FOR AOT "DU" REGULAR ROTARY SLIPS

AOT#	ITEM#	DESCRIPTION	*SPARES	#REQ.	REF.#	WT.
03-102	1	REAR HANDLE	1	1	7613-5195	5.00
03-105	2	HINGE PIN	2	2	7613-A-12	1.25
03-101	3	FRONT HANDLE	2	2	7613-A-157	4.00
03-104	4	LINER RETAINER KEY	3	3	7613-A-52	1.50
03-106	6	FRONT HANDLE PIN	2	2	7613-B-12	.25
03-107	7	REAR HANDLE PIN	1	1	7613-C-12	.38
03-108	8	HINGE SPRING ASSY.	2	2	7613-211	1.25
	9	INSERTS F/DU SEE PAGE 4		18		
03-300	10	SAFETY FLEX HANDLE (UNIVERSAL)		3		5.00

### REPLACEMENT PARTS FOR AOT "DU" LONG ROTARY SLIPS

AOT#	ITEM#	DESCRIPTION	*SPARES	#REQ.	REF.#	WT.
03-102	1	REAR HANDLE	1	1	7613-5195	5.00
03-105	2	HINGE PIN	2	2	7613-A-12	1.25
03-101	3	FRONT HANDLE	2	2	7613-A-157	4.00
03-103	5	LINER RETAINER KEY	3	3	7613-A-67	1.75
03-106	6	FRONT HANDLE PIN	2	2	7613-B-12	.25
03-107	7	REAR HANDLE PIN	1	1	7613-C-12	.38
03-108	8	HINGE SPRING ASSY.	2	2	7613-211	1.25
	9	INSERTS F/DU SEE PAGE 4		24		
03-300	10	SAFETY FLEX HANDLE (UNIVERSAL)		3		5.00

\*RECOMMENDED SPARE PARTS FOR 1 YEAR OPERATION

## INSERTS FOR 4 1/2" "DU" ROTARY TYPE SLIPS AND FOR 4 1/2" "TS-100" SPIDER SLIPS

AOT #	DESCRIPTION	REF.#	WT.	AOT # (SPECIAL FULL FACE INSERTS)
03-120	4 1/2" X 4 1/2"	7613-A-81	.75	03-210
	4 1/2" X 4 3/8"	N/A	.80	03-213
	4 1/2" X 4 1/4"	N/A	.85	03-216
	4 1/2" X 4 1/8"	N/A	.90	03-219
03-121	4 1/2" X 4"	7613-FF-81	1.00	03-221
	4 1/2" X 3 3/4"	N/A	1.75	03-224
03-122	4 1/2" X 3 1/2"	7613-C-82	1.50	03-227
	4 1/2" X 3 3/8"	N/A	1.65	03-229
	4 1/2" X 3 1/4"	N/A	1.75	03-228
	4 1/2" X 3 1/8"	N/A	1.85	03-230
	4 1/2" X 3"	N/A	1.90	03-231
03-123	4 1/2" X 2 7/8"	7613-B-82	2.00	03-233
03-124	4 1/2" X 2 3/8"	7613-A-82	2.25	03-236
03-125	4 1/2" X 2 1/16"	7613-M-82	2.50	03-237
03-126	4 1/2" X 1.900"	7613-H-82	2.75	03-238
03-127	4 1/2" X 1.660"	N/A	2.80	03-239

## INSERTS FOR 5 1/2" "DU" ROTARY TYPE SLIPS AND 5 1/2" "TS-100" SLIPS

AOT #	DESCRIPTION	REF. #	WT.	AOT # (SPECIAL FULL FACE INSERTS)
	5 1/2" X 5 3/4"	N/A	.85	03-241
03-130	5 1/2" X 5 1/2"	7613-H-81	1.00	03-240
03-131	5 1/2" X 5"	7613-G-81	1.50	03-243
	5 1/2" X 4 3/4"	N/A	1.75	03-246
03-132	5 1/2" X 4 1/2"	7613-E-81	2.00	03-249
	5 1/2" X 4 3/8"	N/A	2.10	03-247
	5 1/2" X 4 1/4"	N/A	2.15	03-252
	5 1/2" X 4 1/8"	N/A	2.20	03-255
03-133	5 1/2" X 4"	N/A	2.25	03-258
	5 1/2" X 3 3/4"	N/A	2.28	03-261
03-134	5 1/2" X 3 1/2"	7613-E-82	2.31	03-264
	5 1/2" X 3 1/4"	N/A	2.38	03-266
	5 1/2" X 3 1/8"	N/A	2.45	03-268
	5 1/2" X 3"	N/A	2.52	03-270
	5 1/2" X 2 7/8"	N/A	2.60	03-275
	5 1/2" X 2 3/8"	N/A	2.80	03-277

## INSERTS FOR 7" "DU" ROTARY TYPE SLIPS

AOT #	DESCRIPTION	REF. #	WT.
03-140	7" X 7"	7613-EE-81	1.25
03-141	7" X 6 5/8"	7613-DD-81	1.75
03-146	7" X 5 7/8"	N/A	3.00
03-142	7" X 5 1/2"	7613-Z-81	3.25
03-143	7" X 5"	7613-Y-81	3.75
03-144	7" X 4 1/2"	7613-W-81	4.00

NOTE: "DU" REGULAR REQUIRES 18 INSERTS PER SET  
 "DU" LONG REQUIRES 24 INSERTS PER SET  
 4 1/2" & 5 1/2" "TS-100" SLIPS REQUIRE 12 INSERTS PER SET  
 \* 1 SET INSERTS PER PIPE SIZE RECOMMENDED FOR 1 YEAR SPARES

